

LumEU Flex Professional RGB 800lm-12V







ARTICLE NO. 30-0600-287

Flexible LED-strip with IP 00 protection

PRODUCT FEATURES

- Delivers luminous flux up to 800 lm/m
- Efficient heat management
- Individual setting of colors
- Estimated lifetime L80 > 60.000 hours
- Long lifetime due to high amount of copper in FPC
- With high-quality 3M double adhesive tape



CV	12V	120 	PITCH 8.3 	 250cm Max	 25mm	 120°	 65° TC	L80 60,000	IP00	CE	RoHS
----	-----	---	--	--	--	--	---	---------------	------	----	------

PHOTOMETRIC DATA

Dominant Wavelength	620 nm; 515 nm; 450 nm
Light Color	RGB
Luminous Flux per Meter	W: 800 lm/m R: 120 lm/m G: 500 lm/m B: 100 lm/m
Beam Angle	120 °
Lifetime L80	60.000 hours


ELECTRICAL DATA

Technology	Resistor
Type	SMD3535
Voltage	12 V DC
Electrostatic Discharge	800 V
Power per Meter	28.8 W/m
Operating Temperature	-20~+40 °C
Storage Temperature	-40~+80 °C
Protection	IP 00

MECHANICAL DATA

Length PCB	2500 mm
Width PCB	8 mm
Height PCB	1.8 mm
Cutting Distance	25 mm
LED Distance	8.3 mm
Number of LEDs per Cut	3
Min. Bend Radius	5 cm
Max. Length*	2.5 m

*The value given applies to the application of the rated voltage at the first module section. When using a supply line, the maximum operable length changes depending on the supply line length and its cross section.



These data can have a tolerance value of +/-15%. Typing and printing errors reserved.

Revision: 2 \ 07/2019 \ page 2/2