


LumEU Flex Professional 1000lm/3500K-12V-90

ARTICLE NO. 30-0600-087

Flexible LED-strip with IP 00 protection

PRODUCT FEATURES

- Length 5000 mm
- LED strips for highest demands
- Excellent color rendering: CRI >90
- Long light lines with only one feed through double layer FPC possible
- Estimated lifetime L80 > 60.000 hours
- Current regulation by IC for constant brightness over the entire light line
- With reverse polarity protection diode
- With high-quality 3M double adhesive tape



PHOTOMETRIC DATA

Color Temperature	3500 K
Light Color	White
Luminous Flux per Meter (Center Point 4000K)	1000 lm/m
Luminous Flux per Meter (Effective)	850 lm/m
Efficiency	89 lm/W
Energy Efficiency Class	A+
CRI	>90
Beam Angle	120 °
Lifetime L80	60.000 hours


ELECTRICAL DATA

Technology	IC
Type	SMD2835
Voltage	12 V DC
Electrostatic Discharge	800 V
Power per Meter	9.6 W/m
Operating Temperature	-20~+40 °C
Storage Temperature	-40~+80 °C
Protection	IP 00

MECHANICAL DATA

Length PCB	5000 mm
Width PCB	8 mm
Height PCB	1.2 mm
Cutting Distance	50 mm
LED Distance	8.3 mm
Number of LEDs per Cut	6
Min. Bend Radius	5 cm
Max. Length*	7.5 m

*The value given applies to the application of the rated voltage at the first module section. When using a supply line, the maximum operable length changes depending on the supply line length and its cross section.



These data can have a tolerance value of +/-15%. Typing and printing errors reserved.

Revision: 2 \ 07/2019 \ page 2/2