

LumEU Flex High Protection Professional 2800lm/6500K-24V

ARTICLE NO. 30-2200-217

Flexible LED-strip with IP66 protection due to PUR surface encapsulation

PRODUCT FEATURES

- Length 5000 mm
- Resistant to dust, water jets, UV radiation, abrasion and chemicals
- Estimated lifetime L80 at $T_a < 45^{\circ}\text{C}$ > 60.000 hours
- Connection via 0,2m cable with open ends
- With high-quality 3M double adhesive tape



PHOTOMETRIC DATA

Color Temperature	6500 K
Light Color	Cold White
Luminous Flux per Meter (Center Point 4000K)	2800 lm/m
Luminous Flux per Meter (Effective)	2700 lm/m
Efficiency	93 lm/W
CRI	>90
Beam Angle	120 °
Estimated Lifetime L80 at $T_a < 45^{\circ}\text{C}$	60.000 hours

ELECTRICAL DATA

Technology	IC
Voltage	24 V DC
Electrostatic Discharge	800 V
Power per Meter	28.8 W/m
Operating Temperature	-20~+50 °C
Storage Temperature	-40~+80 °C
Protection	IP 66

MECHANICAL DATA

Length	5000 mm
Width	8 mm
Height	3 mm
Min. Bend Radius	5 cm
Max. Length*	5 m

*The value given applies to the application of the rated voltage at the first module section. When using a supply line, the maximum operable length changes depending on the supply line length and its cross section.

The stated photometric data are typical values, which are influenced by the binning of the LEDs and the encapsulation process. Each of these factors affect the tolerances, therefore the resulting photometric data can deviate from the stated typical values.

All listed data can have a tolerance value of -/+ 15%. Typing and printing errors reserved.